

Engen Transfluid

Transmission Fluid

Description

Engen Transfluid is formulated to withstand the very high pressures encountered in hydrostatic systems. It has a high viscosity index, low pour point and contains special additives to enhance oxidation resistance, rust and corrosion protection, anti-wear and antifoam properties.

Application

Recommended hydraulic fluid for heavily loaded Sunstrand transmissions, particularly in wet environments. It finds application in other hydrostatic and hydrodynamic transmissions used in farm and contractor equipment and industrial machine tools. Engen Transfluid can also be used in place of Type A Suffix A hydrodynamic fluids and as such it is recommended for certain Brockhouse and Twin Disc Powershift transmissions and torque converters.

Benefits

- Excellent oxidation, rust and corrosion protection.
- Prevents wear, stick-slip and chatter.
- High viscosity index and low pour point.
- Fluidity over a wide temperature range.
- Good foam resistance.

Typical Physical Characteristics

Engen Transfluid	
Viscosity, cSt @ 40 °C	42,9
Viscosity, cSt @ 100 °C	7,0
Viscosity Index	100
Flash Point, °C	178
Pour Point, °C	-33

02.2015

Due to continual product research and development, the information contained herein is subject to change without notification. Refer to the Material Safety Data Sheet (MSDS) for information on the safe handling and use of this product.

Engen Petroleum Ltd | Tel: 08600 36436 | Website: www.engenoil.com | Email: 1call@engenoil.com