

Parprol 150

Paraffinic Process Oil

Description

Parprol 150 is a general purpose medium viscosity paraffinic process oil.

Application

Parprol 150 is particularly suited to the following applications:

- Rope dressing
- Adhesives
- Rubber extenders
- Plasticizers

Typical Product Specification

Parprol 150	
Viscosity, cSt at 40°C min	105
Viscosity, cSt at 40°C max	130
Viscosity Index	95
Colour, ASTM	4
Flash Point, °C	230
Pour Point, °C	-6

Physical Properties

Property	Units	Test Method	Parprol 150
VCG		ASTM D2501	0.808
Unsulphonated residue	%v/v	ASTM D483	87
Analine point	°C	ASTM D611	104
Carbon Type			
Aromatics	%	Sun-Oil	6
Naphthenics	%		26
Paraffinics	%		68
Sulphur	%m/m	ASTM D2622	0.6
Neutralisation Number	mg KOH/g	ASTM D664	0.03
Density, 20 °C	kg/l	ASTM D1298	0.879

10.2015

Due to continual product research and development, the information contained herein is subject to change without notification. Refer to the Material Safety Data Sheet (MSDS) for information on the safe handling and use of this product.

Engen Petroleum Ltd | Tel: 08600 36436 | Website: www.engenoil.com | Email: 1call@engenoil.com