

# Parprol 22

Paraffinic Process Oil

## Description

Parprol 22 is a general purpose paraffinic process oil.

## Application

Parprol 22 is particularly suited to the following applications:

- Process oil for natural, SBR and butyl rubber
- Softener for leather
- Plasticiser for ethyl cellulose
- Ink oil
- Textile batching oil

## Typical Product Specification

Parprol 22	
Viscosity, cSt at 40°C min	18
Viscosity Index	95
Colour, ASTM	3
Flash Point, °C	180
Pour Point, °C	-15

## Physical Properties

Property	Units	Test Method	Parprol 22
VCG		ASTM D2501	0.810
Unsulphonated residue	%v/v	ASTM D483	93
Analine point	°C	ASTM D611	101
Carbon Type			
Aromatics	%	Sun-Oil	3
Naphthenics	%		28
Paraffinics	%		69
Sulphur	%m/m	ASTM D2622	0.8
Neutralisation Number	mg KOH/g	ASTM D664	0.01
Density, 20 °C	kg/l	ASTM D1298	0.864

09.2015

Due to continual product research and development, the information contained herein is subject to change without notification. Refer to the Material Safety Data Sheet (MSDS) for information on the safe handling and use of this product.

Engen Petroleum Ltd | Tel: 08600 36436 | Website: [www.engenoil.com](http://www.engenoil.com) | Email: [1call@engenoil.com](mailto:1call@engenoil.com)