

Parprol 32

Paraffinic Process Oil

Description

Parprol 32 is a general purpose paraffinic process oil.

Application

Parprol 32 is particularly suited to the following applications:

- Process oil for butyl rubber
- Rope dressing
- Ink oil
- Textile batching oil

Typical Product Specification

Parprol 32	
Viscosity, cSt at 40°C min	28
Viscosity, cSt at 40°C max	32
Viscosity, cSt at 100°C	5.158
Viscosity Index	95
Colour, ASTM	3
Flash Point, COC, °C min	228
Pour Point, °C max	-12
Refractive Index @ 20° C, max	1.48

Physical Properties

Property	Units	Test Method	Parprol 32
VCG		ASTM D2501	0.822
Unsulphonated residue	%v/v	ASTM D483	87
Aniline point	°C	ASTM D611	104
Carbon Type			
Aromatics	%	Sun-Oil	4
Naphthenics	%		26
Paraffinics	%		70
Sulphur	%m/m	ASTM D2622	0.4
Neutralisation Number	mg KOH/g	ASTM D664	0.02
Density, 20 °C	kg/l	ASTM D1298	0.874

07.2016

Due to continual product research and development, the information contained herein is subject to change without notification. Refer to the Material Safety Data Sheet (MSDS) for information on the safe handling and use of this product.

Engen Petroleum Ltd | Tel: 08600 36436 | Website: www.engenoil.com | Email: 1call@engenoil.com